

## Key Features

- Universal wide-range power input - AC / DC
- Mountable on DIN rail TS35 / 7.5 or 15
- Protected against overload, over voltage, temperature overload and short circuit
- LED indication for power supply
- 100% solid load



## Technical Data

- |                         |  |
|-------------------------|--|
| ▪ Device output voltage | 24 VDC / 48W   |
| ▪ min./max. Current     | 0 A / 2 A  |
| ▪ Device input voltage  | 85 ~ 264 VAC / 120 ~ 370 VDC   |
| ▪ Frequency range       | 47 ~ 63 Hz   |
| ▪ Temperature           | Operation: -10 ~ 50°C   Storage: -20 ~ 85°C  |
| ▪ Humidity              | Operation: 20 ~ 90%   Storage: 10 ~ 95%  |
| ▪ Connections           | Input: 3-pin<br>Output: 4-pin screw terminal   |
| ▪ Approvals             | UL 508, c-UL, TÜV EN60950, CB, CE<br>EN 55022 Class B / EN 61000-3-2,<br>EN 61000-4-2,3,4,5,6,8,11 / ENV50204 /<br>EN55024 / EN61000-6-2 |
| ▪ Dimensions            | 93 x 78 x 67 mm  |
| ▪ Weight                | 0,31 kg  |
| ▪ Item no.:             | 316411   |