

# Sagemcom



## Siconia® Self-Contained Watthour meter

Type S162LW and S163LW

SPECIFICATIONS		
Basic Features	Service Type:	FM16S
	Rated Voltage:	4W WYE 120/208V – 277/480V 4W Delta 120(208)/240V – 240(416)/480V
	Frequency:	60 Hz (+/-15%)
	Current Class:	CL200 or CL320
	Operating System:	Linux
	Real time clock:	Less than 0,5s /day @ 23°C (5,78 ppm) Drift < 0,15s /°K /24h Time stamp maintained for 2 years, by battery
	Last Gasp:	Power outage notification up to 90 seconds
	Accuracy for active energy:	In conformance with ANSI C12.1 and ANSI C12.20 CA 0.2 (accuracy class 0,2%)
	Accuracy for reactive energy:	In conformance with IEC 62053-24 Cl. 1 (accuracy class 1%) Current range 1,5 - 30 (210) A
	Power Consumption:	@ Nominal Voltage Less than 1,5W / 2,5VA (without communication) 4,5W / 6,0VA (max value)
Environment	Events Management:	<b>Configurable event logbooks</b> <ul style="list-style-type: none"> <li>Standard event</li> <li>Fraud detection event</li> <li>Power Quality event</li> <li>Communication event</li> <li>Technical parameters change event</li> </ul>
	Operating temperature inside the meter:	-40°C ... +85°C HR <95%, non-condensing
Customer Interaction	Temperature sensor:	Metrology compensation
	Graphical LCD Display:	Energy registers on 9 digits in kWh (more than 20 years without rollover) Voltage and current presence and direction Quadrant information Display scroll sequence programmable (factory or end user) Push Button in front face or Light sensor, which acts like a push button
	Home area network:	Wi-Fi enabled supporting Matter protocol Gird Apps enabled In home Intelligence Apps enabled
Communication interface	Optical communication port:	ANSI Type 2 optical Port Protocol in conformance with ANSI C12.18 9600 or 19200 bauds Mechanical interface in conformance with ANSI C12.10
	Modular Wide Area Network Communication module:	In conformance with ANSI C12.22 and ANSI C12.19 supporting LTE Cat.M1 and RF Wi-Sun

## Technical features

### TIME OF USE

- Calendar with 12 season-profiles, 4 week-profiles and 24 day-profiles
- 30 special days
- 8 registers rates
- Up to 36 Billing registers

### POWER QUALITY

- In conformance with the IEC 61000-4-30 standard class A
- Integrated on 12 periods (200ms @60Hz)
- Harmonics up to rank 50
- Dip, swell and voltage interruption
- Voltage unbalance
- Rapid voltage change
- Voltage harmonics by rank and THD
- UTC time synchronization

### CONFIGURABLE LOAD PROFILES

- 3 Load profiles concurrent storage
- 50 configurable data channels
- Capture period configurable between 1 and 60 min

### GRID-EDGE COMPUTING

- Device Identification
- Power distribution monitoring

### WAVEFORM

- Voltage and Current integrated over a period
- Data sampling: 16 ksp/s

## Security

### DATA ENCRYPTION

- AES standard
- Cryptographic functions
- Firmware update over the air (FOTA) with signature management

### SAFETY

- In conformance with ANSI C12.1 and UL2735
- Impulse voltage 6kV in conformance with IEC 61180-1
- Surge 4kV in conformance with IEC 61000-4-5

### ANTI-TAMPER

- Super-Magnet detection
- Top Cover insertion/removal survey
- Motion detection

### CONNECTION

