

Sagemcom



SICONIA® SM - wM-Bus

Compact ultrasonic water meter for cold and hot water, combining high measurement accuracy and data communication for submetering and primary metering applications.

The SICONIA® SM water meter delivers a **measurement error close to 0%** across a wide flow range. Its **ultrasonic technology** eliminates all moving mechanical parts inside the meter, removing mechanical wear effects that could affect metrological performance over time. As a result, billing remains accurate and reliable throughout the meter's lifetime.

The SICONIA® SM wM-Bus water meter enables remote data transmission through either drive-by/mobile reading or fixed network AMR/AMI systems. This ensures rapid reporting of critical alarms and supports daily monitoring of consumption data.

Technical features

TECHNICAL CERTIFICATIONS

- ISO 4064
- MID and OIML R49
- EN 13757

DRINKING WATER CERTIFICATIONS

- Large portfolio of drinking water certifications, including in particular:
 - WRAS
 - ACS
 - DM174
 - HYDROCHECK
 - KIWA
- Compliant with the European Drinking Water Directive (DWD)

COMMUNICATION



- wM-Bus 868MHz

CYBERSECURITY

- Security by Design approach
- Compliance with European regulations: NIS 2, Cyber Resilience Act (CRA), etc.
- Data encryption

SMART NETWORK MONITORING

- Early leak detection and loss reduction
- Ambient and water temperature monitoring
- Advanced protection against fraud and tampering
- Backflow detection and measurement

ENERGY

- Lithium battery
- Up to 15 years lifetime*

ENVIRONMENT

- Protection class IP67
- Ambient temperature : -20°C to +70°C


**Depends on configuration and environmental conditions*

Metrology

SICONIA® SM	
DN15	
Accuracy class	Class 2
Permanent flow rate : Q3	2.5 m³/h
Starting flow	2 l/h
R ratio (Q3/Q1)	R250
Nominal pressure	16 bars
Temperature class	T30 (cold water), T70 (hot water)
Measuring frequency	8 flow measurements per second
Mounting in any position	H, V, H/V
Sensitive class	U0/D0

Dimensions


SICONIA® SM	
Thread G3/4"	
A (mm)	58
B (mm)	14
C (mm)	80.6
D (mm)	110
E (mm)	91.5
Materials	Composite (PPS 40%GF)



LCD Interface

The complete SICONIA® SM water meter range features an LCD display. With its 10-digit register (7 integer digits and 3 decimal digits), it ensures highly accurate reading and offers a display capacity that exceeds the requirements of the Measuring Instruments Directive (MID).

1	The measured volumes are indicated in m³, associated with 3 decimal places giving an indication in liters
2	Animated icons showing when there is an active flow through the meter
3	MID certified information
4	The meter is in a backflow situation
5	The pipe is not filled with water
6	One or more events/alarms are currently active
7	RF status information
8	Battery level information



All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom Energy & Telecom tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Simplified joint stock company Capital 36 626 034,60 Euros - 518 250 337 RCS Nanterre. 10/2026